

RECORDING MEDIUM, REPRODUCTION DEVICE, RECORDING METHOD,
PROGRAM, REPRODUCTION METHOD

Publication number: WO2004077827

Publication date: 2004-09-10

Inventor: YAHATA HIROSHI; OKADA TOMOYUKI; IKEDA
WATARU; MCCROSSAN JOSEPH

Applicant: MATSUSHITA ELECTRIC IND CO LTD (JP); YAHATA
HIROSHI; OKADA TOMOYUKI; IKEDA WATARU;
MCCROSSAN JOSEPH

Classification:

- international: G11B27/034; G11B27/10; G11B27/30; G11B27/32; G11B27/34; H04N5/92; H04N5/85; G11B27/031; G11B27/10; G11B27/30; G11B27/32; G11B27/34; H04N5/92; H04N5/84; (IPC-1-7): H04N5/92; G06F3/14; H04N5/93

- European: G11B27/034; G11B27/10A1; G11B27/30C;
G11B27/32D2; G11B27/34; H04N5/92N4

Application number: WO2004/JP02343 20040227

Priority number(s): JP20030052838 20030228; JP20030280706 20030728;
US20030485207P 20030703

Also published as:

EP1619891 (A1)
EP1605696 (A1)
WO2004077826 (A1)
CA2515517 (A1)


Cited documents:

WO9821722
JP2001332006

[Report a data error here](#)

Abstract of WO2004077827

A BD-ROM contains AVClip obtained by multiplexing a moving picture stream and an interactive graphics stream. The interactive graphics stream displays an interactive screen containing a graphical button member by combining with the moving picture. The interactive graphics stream contains arrangement of the state control information (ICS) and a plurality of graphics data (ODS). The initial display timing of the interactive screen is the time obtained as the sum of a predetermined period and a decode end time (PTS) of the graphics data (S-ODSfirst, S-ODSlast) positioned in the middle of the graphics data arrangement. The state control information is stored in a PES packet and the PES packet contains a time stamp (PTS). The PTS indicates the initial display timing of the interactive screen.



Data supplied from the *esp@cenet* database - Worldwide